



东莞市速业精密机械有限公司

马力 HP-4P	减速比 RATIO	型号 SHAFT DIAMETER	A	D	E	F	G	H	J	K	L	M	X	Y	重量KG
100W 1/8HP	3-50	18	168	40	110	135	65	9	16	45	10	72.5	132	88.5	3
	60-200	22	200	65	130	160	90	11	18.2	56	15	80	152	97.5	4
200W 1/4HP	3-10	18	168	40	110	135	65	9	16	45	10	72.5	132	88.5	3
	15-90	22	200	65	130	160	90	11	18.2	56	15	80	152	97.5	5
	100-200	28	258	90	140	180	120	11	20.8	65	15	95.2	180	116	7
400W 1/2HP	3-10	22	207	65	130	160	90	11	18.2	56	15	80	152	97.5	6
	15-90	28	263	90	140	180	120	11	20.8	65	15	95.2	180	116	7
	100-200	32	300	130	170	215	160	13	30.2	76	25	108.5	210	138.5	12.6
750W 1HP	3-25	28	269	90	140	180	120	11	20.8	65	15	95.2	180	116	7
	30-120	32	310	130	170	215	160	13	30.2	76	25	108.5	210	138.5	14.6
	125-200	40	336	150	210	260	185	15	42.2	80	25	117.8	248	160	35
1500W 2HP	3-25	32	320	130	170	215	160	13	30.2	76	25	108.5	210	138.5	14.6
	30-120	40	350	150	210	260	185	15	42.2	80	25	117.8	248	160	35
2200W 3HP	3-60	40	360	150	210	260	185	15	42.2	80	25	117.8	248	160	35
	70-120	50	410	170	265	330	220	19	51.7	104	30	148.6	315	200	43
3700W 5HP	3-25	40	360	150	210	260	185	15	42.2	80	25	117.8	248	160	35
	30-80	50	410	170	265	330	220	19	51.7	104	30	148.6	315	200	43

## 输入轴SHAFT

## 键槽KEYWAY

## 键KEY

KW S1h6 P1 W1 T1 Q1 SPEC

0.1/0.2 14 30 5 16 26 5×5×25

0.4 14 30 5 16 26 5×5×25

0.75 19 40 6 21.5 35 6×6×35

1.5 24 50 8 27 45 8×7×45

2.2 28 60 8 31 50 8×7×50

3.7 28 60 8 31 50 8×7×50

## 输出轴SHAFT

## 键槽KEYWAY

## 键KEY

Sh6 P W T Q SPEC

Φ18 30 5 20 25 5×5×25

Φ22 40 7 25 35 7×7×35

Φ28 45 7 31 40 7×7×40

Φ32 55 10 35.5 50 10×8×50

Φ40 65 10 43.5 60 10×8×60

Φ50 80 14 54 75 14×9×75

出力轴尺寸

INPUT SHAFT SIZE

出力轴尺寸

OUTPUT SHAFT SIZE

